

Illuminated contact block, momentary, W2x4,6d BZLII_AU

Description:	gold-plated
Category:	Contact blocks
Series:	Contact blocks BZ...
Protection class:	II (protective insulation)
Degree of protection:	IP00
Switching function:	momentary action
Travel:	3 mm
Illumination:	yes
With labelling option:	no
Contact equipment:	2 NO
Connection type:	Faston terminals 2.8 x 0.8 mm
Accessory type:	contact block
Electrical life:	1 million switching cycles at rated load
Storage temperature:	-50°C ... 85°C
Mechanical life:	1 million switching cycles
Positive opening:	no
Operating temperature:	-30°C ... 70°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LEDs
Contact material:	AgNi, gold-plated
Lamp socket:	W2x4,6d


Necessary accessory



Ultra-bright LED, W2x4,6d socket, 12V L2X4,6-12UW



Ultra-bright LED, W2x4,6d socket, 24V L2X4,6-24UW



Optional accessory



Double Faston FD2,8



Faston clamp 2.8 x 0.8 mm with snap-in pin FH2,8



Insulating case IH2,8



Voltage reducer to operate an LED at 230V AC VE_LED230_S



Plug-in socket with 6 contacts (2) XAP611

