

**BTLI**

28.06.2021

**Illuminated Contact Block, momentary**



General Data	
Type reference	BTLI
Description	Illuminated contact block
Approvals	CCC, cCSAus, DNVGL, ENEC10, VDE, CE, UKCA, UR
Contact type	2 NO
Degree of protection	IP00
Operation travel	3 mm
Connection type	Faston terminals 2.8 x 0.8 mm
Contact material	AgNi
Max. storage temperature	-50°C ... 85°C
Max. operating temperature	-30°C ... 70°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LEDs
Mechanical life	1 million switching cycles
Electrical life (rated load)	1 million switching cycles
Contact resistance NO	< 20 mOhm (new state)
Min. current	1 mA (under laboratory conditions)
Min. voltage	5 V
Bouncing time NO	< 10ms

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)		
	alternate current	direct current
Utilisation category	AC15 B300	DC13 Q300
Rated insulation voltage Ui	250 V	300 V
Rated operating voltage Ue	250 V	250 V / 125 V / 60 V / 24 V
Rated operating current Ie	1.5 A	0.2 A / 0.4 A / 1 A / 2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	6 A	-

Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)	
Rated voltage Ue	250 V~



Rated current  $I_e$  6(4) A

### Technical Data - Lamp

Lamp socket W2x4,6d

Max. lamp voltage 60 V

Max. lamp output 1.2 W

Definition X1...anode, X2...cathode

### Additional electrical data

Overvoltage category II

### Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	DC13	-
Rated insulation voltage $U_i$	-	-
Rated operating voltage $U_e$	12 V	-
Rated operating current $I_e$	6 A	-
Breaking capacity	1,1Ie	-
Continuous thermal current	-	-

### Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)

Rated voltage  $U_e$  12 V DC

Rated current  $I_e$  6[6] A

### Data cc. to UL508/ CSA 22.2 No. 14-18

Rating B300, Q300 pilot duty

Lamp rating 1.2 W, 60 V max



