

FRTLII_C122

16.01.2023

Illuminated contact block with 5-pole M12 connector, momentary



General Data

Type reference	FRTLII_C122
Description	Contact block with M12 connector, detent collar, illumination option
Approvals	CE, UKCA
Contact type	2 NO
Degree of protection	IP00
Connection type	5-pole M12 connector (integrated), A coded, AIDA
Contact material	AgNi
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	600,000 switching cycles
Electrical life (rated load)	600,000 switching cycles at rated load
Contact resistance NO	< 50 mOhm (new state)
Min. current	6 mA
Min. voltage	5 V
Bouncing time NO	< 10ms

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15	DC13
Rated insulation voltage Ui	50 V	50 V
Rated operating voltage Ue	35 V	35 V
Rated operating current Ie	2 A	2 A
Breaking capacity	-	-
Continuous thermal current	2 A	2 A

Technical Data - Lamp

Lamp socket	none, with integrated 3 mm LED white
Max. lamp voltage	30 V AC/DC



Max. lamp output

14 mA (at 24 V DC)

Additional data

Mounting position any

Standards EN 60947-5-1

Tightening torque (M12-connector) max. 0.4 Nm

B10d [cycles] depending on the pushbutton/switch head

Material group I

Overvoltage category II

Pollution degree 2

Note

I = NO contact

Pin assignment:

Pin 1 Pin 2 Pin 3 Pin 4 Pin 5 Type

NO 1 NO 2 LED - NO 1 COM (NO 2, LED +) 2 NO + LED (AIDA)

Safety instructions / mounting instructions

- the M12 connector must not be connected or disconnected under load

- the single connector pin may be loaded with max. 2 A

- not suitable for use under water

- there may not be any mechanical load on the M12 connector, ensure that there is sufficient strain relief!

- observe the operating instructions

Depending on the usage the signal lamp connected to the common pin must be considered in the overall system.



