

FRVKOO_C111

02.11.2021

Emergency-stop with 5-pole M12 connector AIDA



General Data

Type reference	FRVKOO_C111
Description	Emergency-stop, foolproof with integrated M12 connector
Approvals	CE, cURus, TÜV_Süd, UKCA
Contact type	2 NC
Protection class	II (protective insulation)
Degree of protection	IP65 / IP67 (in the front); IP65 / IP67 (on the rear with plugged-in M12 connector)
Connection type	5-pole M12 connector (integrated), A coded, AIDA
Contact material	AgNi
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	50,000 switching cycles
Electrical life (rated load)	50,000 switching cycles at rated load
Contact resistance NC	< 50 mOhm (new state)
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15	DC13
Rated insulation voltage Ui	50 V	50 V
Rated operating voltage Ue	35 V	35 V
Rated operating current Ie	2 A	2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	2 A	2 A

Additional data

Mounting aperture	22.3 mm
Tightening torque (mounting nut)	1.0 ... 1.7 Nm



Tightening torque (M12-connector)	max. 0.4 Nm
Mounting position	any
Standards	EN 60947-5-1, EN 60947-5-5, EN ISO 13850
Release	twist release, left or right
Ld	20% (NC)
B10d [cycles]	226.000
Material group	I
Overvoltage category	II
Pollution degree	2

Note

O = NC contact
With switching position indicator

Pin assignment
xx Pin 1 Pin 2 Pin 3 Pin 4 Pin5
11 NC(11) NC(21) n.c. NC(12) NC(22)

Safety instructions / mounting instructions
- the connector must not be connected or disconnected under load
- the single connector pin may be loaded with max. 2 A
- not suitable for use under water
- when used outdoors, the M12 connections must be protected against corrosion separately

Data acc. to UL/IEC 60947-5-5

Ratings	Silver: 35V AC/DC 2A Ith 2A, Ui 50V Gold: 35V AC/DC/100mA
Torque	1.0 ... 1.7 Nm (head nut)
Enclosure Type	Type 4X (indoor) front face



