

IKS15

16.03.2009


General Data

Type Reference	IKS15
Description	Fuse terminal
Approvals	Demko, CE, UKCA, UR
Terminal type	Fuse terminal incl. fuseholder for 5x20 mm fuses
Terminal width	8.1 mm
Mounting method	top hat rail N35, EN60715 TH35
Connection type	screw connection, slotted screw
Thread size of screw connection	M3
Torque	0.5 Nm
Rated cross section	4 mm ²
Wire size (solid)	0.5 ... 6 mm ²
Wire size (stranded)	0.5 ... 4 mm ²
Rated voltage	250 V
Rated current	6.3 A
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-30°C ... 40°C

Photo

Data acc. to IEC 60947-7-1

Flammability class acc. to UL94	V2
Pollution degree	3
Overvoltage category	III
Material group	II
Rated impulse voltage	4 kV
Insulating material	PA 6.6
Stripping length	7 mm

Data acc. to IEC 60947-7-3

Power dissipation (single arrangement)	1.6 W
--	-------



Power dissipation (compound arrangement) 1.6 W

Data acc. to UL1059

Torque 10 Lb In

Wire size (solid) 14-22 AWG

Rated voltage 300 V

Rated current 10 A

Data acc. to UL4248-1

For fuses with max. interrupting rating

Wire size

Torque

Voltage

Current

For fuse type

