

Pedal switch with domed protection cover



General Data	
Type reference	KEFBM
Description	Pedal switch in a light metal casing + protective cover equipped with ET contact block
Approvals	CE, UKCA
Contact type	1 NC + 1 NO
Degree of protection	IP00
Operation travel	6 mm
Connection type	screw connection 2x2.5 mm ² , finger-protected acc. to BGVA3
Contact material	AgNi
Max. storage temperature	-50°C ... 70°C
Max. operating temperature	-30°C ... 70°C
Mechanical life	1 million switching cycles
Electrical life (rated load)	switching cycles: 1 million at 250 V/10(6) A 250,000 at 250 V/16(10) A 500,000 at 250 V/5 A (AC15)
Contact resistance NO	< 20 mOhm (new state)
Contact resistance NC	< 20 mOhm (new state)
Bouncing time NO	< 10ms
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)		
	alternate current	direct current
Utilisation category	AC15	DC13
Rated insulation voltage U _i	400 V	400 V
Rated operating voltage U _e	400 V / 250 V	400 V / 250 V / 125 V / 60 V / 24 V
Rated operating current I _e	3 A / 5 A	0.12 A / 0.2 A / 0.4 A / 1 A / 2 A
Breaking capacity	10I _e	1,1I _e
Continuous thermal current	10 A	-



Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)

Rated voltage U _e	250 V~ / 440 V~
Rated current I _e	10(6) A / 6(3) A

Additional data

Degree of protection (complete type)	IP65
Cable entry	M16 x 1.5

Note

includes the contact block ET

