



minibox with M12 cable entry (8 poles) with emergency-stop and pushbutton MBM128_NOOIT1

Description:

Lenses and nameplates to be ordered separately.
 Operating temperature: -25 °C...+70 °C Storage temperature: -25°C...+85 °C Switch type: emergency stop: 2 NC (positive opening), 1 NO pushbutton: 1 NO Fixation: with fastening clip on the rear Connection: M12 8 poles (m) Pos. 1 (emergency-stop) NC 1, pin 1-2; NC 2, pin 3-4; NO, pin 5-6 Pos. 2: (pushbutton) NO, Pin 7-8 Contact material: AgNi, gold-plated 5µm Electr./mech. life: emergency stop: 50.000 at rated load (ambient temp. = 20°C) pushbutton: 1 million (ambient temp. = 20°C) Positive opening: opening contact acc. to EN 60947-5-1, appendix K Test voltage M12 plug: 1.5kV Electrical Data Operating voltage: 1V... 36V Operating current: 1mA ... 250mA

Category:	Equipped insulated plastic enclosures
Series:	minibox
Degree of protection:	IP65
Illumination:	no
With labelling option:	no
Colour	dark-grey bottom part/yellow cover
Anti-lock collar:	no
Release:	twist right or left
Switching position indicator:	yes
Foolproof:	yes
Contact material:	AgNi / AgNi, gold-plated 5µm (_AU)
Equipped:	yes