

**MZTO**

18.05.2021

**Modular Contact, momentary,  
for base-plate mounting**



**General Data**

Type reference	MZTO
Description	Modular contact block (positive opening contact), base-plate mounting
Approvals	CCC, ENEC05, KEMA, CE, UKCA
Contact type	1 NC
Degree of protection	IP20
Operation travel	6 mm
Connection type	screw connection 2x 2.5 mm <sup>2</sup>
Contact material	AgNi
Max. storage temperature	-50°C ... 85°C
Max. operating temperature	-30°C ... 85°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LEDs
Mechanical life	1 million switching cycles
Electrical life (rated load)	1 million switching cycles at rated load
Contact resistance NO	< 20 mOhm
Contact resistance NC	< 20 mOhm
Min. current	1 mA (under laboratory conditions)
Min. voltage	5 V
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

**Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)**

	alternate current	direct current
Utilisation category	AC15 A600	DC13 Q600
Rated insulation voltage Ui	600 V	600 V
Rated operating voltage Ue	240 V / 440 V	440 V / 250 V / 125 V / 60 V / 24 V
Rated operating current Ie	3 A / 1.6 A	0.12 A / 0.2 A / 0.4 A / 1 A / 2 A
Breaking capacity	10Ie	1,1Ie



Continuous thermal current

16 A

**Electrical data acc. to IEC/EN 61058-1 (VDE 0630 Sect. 1)**

Rated voltage U<sub>e</sub>

250 V~ / 440 V~

Rated current I<sub>e</sub>

16(10) A / 10(6) A

**General data**

Tightening torque (screw terminal)

0.8...1.0 Nm

