











I= Switching position >= Spring return

Selector head, maintained RRJVAWB

Category: Selector switches (momentary/maintained)

Series: RONTRON-R-JUWEL

Panel cut-out: Ø 22.3 mm

Protection class: II (protective insulation)

Degree of protection: IP65

Switching function: maintained action

Illumination: no With labelling option: no

Front bezel stainless steel, polished

Positive opening: no Shape: round

Optional accessory



AS-Interface slave ASI_BZ



Contact block, momentary AZ2N



Contact block, momentary AZ4I



Contact block, momentary AZ4O



Contact block, momentary BZII





Contact block, momentary BZIIK



Contact block, momentary BZIIK_AU



Contact block, momentary BZII_AU



Contact block, momentary BZOI



Contact block, momentary BZOIK



Contact block, momentary BZOIK_AU



Contact block, momentary BZOI_AU



Contact block, momentary BZOO





Contact block, momentary BZOOK



Contact block, momentary BZOOK_AU



Contact block, momentary BZOO_AU



Contact block, momentary BZ_439



Contact block, momentary BZ_439_AU



Contact block, momentary BZ_494



Contact block with two-piece plunger, momentary CT2_549



Contact block with two-piece plunger, momentary CZTP2_549





Insulated plastic enclosure, 1 mounting hole DIRL1V-R22



Insulated plastic enclosure, 1 mounting hole DIRL1VGB-R22



Insulated plastic enclosure, 2 mounting holes DIRL2V-R22



Insulated plastic enclosure, 3 mounting holes DIRL3V-R22



Insulated plastic enclosure, 3 resp. 4 mounting holes DIRL4V-R22



Insulated plastic enclosure, 1 mounting hole IRL1M



Insulated plastic enclosure, 1 mounting hole IRL1M_GELB



Insulated plastic enclosure, 2 mounting holes IRL2M





Insulated plastic enclosure, 3 mounting holes IRL3M



Insulated plastic enclosure, 5 mounting holes IRL5M



External nameplate holder RRJABT



Insulated plastic enclosure with 1 mounting hole SIL22/1



High insulated plastic enclosure with 1 mounting hole SILH22/1