











legend
I= Switching position >=
Spring return

Illuminated selector head, left maintained, right momentary RRJWCL KL

Category: Selector switches (momentary/maintained)

Series: RONTRON-R-JUWEL

Panel cut-out: Ø 22.3 mm

Protection class: II (protective insulation)

Degree of protection: IP65

Switching function: momentary and maintained action

Illumination: yes With labelling option: no

Front bezel silver-coloured

Knob colour clear
Positive opening: no
Shape: round

Optional accessory



AS-Interface slave with T5,5K socket ASI_BZL5



Illuminated contact block, momentary AZL41



Illuminated contact block, momentary AZL4O



Illuminated contact block, momentary, T5,5K BZL5_439





Illuminated contact block, momentary, T5,5K BZL5_439_AU



Illuminated contact block, momentary, W2x4,6d BZLII



Illuminated contact block, momentary, T5,5K BZLII5



Illuminated contact block, momentary, T5,5K BZLII5K



Illuminated contact block, momentary, T5,5K BZLII5K_AU



Illuminated contact block, momentary, T5,5K BZLII5_AU



Illuminated contact block, momentary, W2x4,6d BZLIIK



Illuminated contact block, momentary, W2x4,6d BZLIIK_AU





Illuminated contact block, momentary, W2x4,6d BZLII_AU



Illuminated contact block, momentary, W2x4,6d BZLOI



Illuminated contact block, momentary, T5,5K BZLOI5



Illuminated contact block, momentary, T5,5K BZLOI5K



Illuminated contact block, momentary, T5,5K BZLOI5K_AU



Illuminated contact block, momentary, T5,5K BZLOI5_AU



Illuminated contact block, momentary, W2x4,6d BZLOIK



Illuminated contact block, momentary, W2x4,6d BZLOIK_AU





Illuminated contact block, momentary, W2x4,6d BZLOI_AU



Illuminated contact block, momentary, W2x4,6d BZLOO



Illuminated contact block, momentary, T5,5K BZLOO5



Illuminated contact block, momentary, T5,5K BZLOO5K



Illuminated contact block, momentary, T5,5K BZLOO5K_AU



Illuminated contact block, momentary, T5,5K BZLOO5_AU



Illuminated contact block, momentary, W2x4,6d BZLOOK



Illuminated contact block, momentary, W2x4,6d BZLOOK_AU





Illuminated contact block, momentary, W2x4,6d BZLOO_AU



Illuminated contact block, momentary, W2x4,6d BZL_439



Illuminated contact block, momentary, W2x4,6d BZL_439_AU



Illuminated contact block, momentary CTL2



Illuminated contact block with separate plungers, momentary CTL2_549



Illuminated contact block with two-piece plunger CZTLP2_549



Insulated plastic enclosure, 1 mounting hole DIRL1V-R22



Insulated plastic enclosure, 1 mounting hole DIRL1VGB-R22





Insulated plastic enclosure, 2 mounting holes DIRL2V-R22



Insulated plastic enclosure, 3 mounting holes DIRL3V-R22



Insulated plastic enclosure, 3 resp. 4 mounting holes DIRL4V-R22



Insulated plastic enclosure, 1 mounting hole IRL1M



Insulated plastic enclosure, 1 mounting hole IRL1M_GELB



Insulated plastic enclosure, 2 mounting holes IRL2M



Insulated plastic enclosure, 3 mounting holes IRL3M





Insulated plastic enclosure, 5 mounting holes IRL5M



LED light ring for status indication or additional illumination LR22K_24B



LED light ring for status indication or additional illumination LR22K_24G



LED light ring for status indication or additional illumination LR22K_24R



RGB LED light ring for status indication or illumination LR22K_24RGB



Two-coloured alternate LED-illuminated ring for status indication LR22K_24R_G



LED light ring for status indication or additional illumination LR22K_24W





LED light ring for status indication or additional illumination $LR22K_24Y$



External nameplate holder RRJABT



Insulated plastic enclosure with 1 mounting hole SIL22/1



High insulated plastic enclosure with 1 mounting hole SILH22/1

